



118 SERİSİ

DİJİTAL KUMPAŞ




118-012-14

- ◆ Çözünürlük: 0.01mm/0.0005"
- ◆ Butonlar: on/off, zero, mm/inç, ABS
- ◆ Veri çıkışı (Kablo kodu:100-11 veya 100-12)
- ◆ Otomatik açma/kapanma
- ◆ Paslanmaz çelik




birim: mm



Sonuç= değer+10mm

Kod	Aralık	Hassasiyet	a	c	h	L
118-008-11	0-200mm/0-8"	±0.03mm	12	17	60	320
118-012-14	0-300mm/0-12"	±0.04mm	12	17	60	420
118-012-15	0-300mm/0-12"	±0.04mm	12	17	90	420




Dış ölçümler


İç ölçümler
(boy>10mm)

118 SERİSİ


DİJİTAL KUMPAŞ



118-020-11




birim: mm



Sonuç= değer+20mm

Kod	Aralık	Hassasiyet	a	c	h
118-012-11	0-300mm/0-12"	±0.04mm	18	24	100
118-012-12	0-300mm/0-12"	±0.05mm	18	24	150
118-012-13	0-300mm/0-12"	±0.05mm	18	24	200
118-020-11	0-500mm/0-20"	±0.05mm	18	24	100
118-020-12	0-500mm/0-20"	±0.06mm	18	24	150
118-020-13	0-500mm/0-20"	±0.06mm	18	32	200
118-020-14	0-500mm/0-20"	±0.08mm	18	42	300
118-024-11	0-600mm/0-24"	±0.05mm	18	24	100
118-024-12	0-600mm/0-24"	±0.06mm	18	24	150
118-024-13	0-600mm/0-24"	±0.06mm	18	32	200
118-024-15	0-600mm/0-24"	±0.08mm	18	42	300
118-040-11	0-1000mm/0-40"	±0.08mm	24	32	150
118-040-12	0-1000mm/0-40"	±0.08mm	24	32	200
118-040-13	0-1000mm/0-40"	±0.10mm	24	42	300
118-060-11	0-1500mm/0-60"	±0.11mm	24	42	150
118-080-11	0-2000mm/0-80"	±0.14mm	24	42	150



Dış ölçümler

İç ölçümler
(size>20mm)

- ◆ Çözünürlük: 0.01mm/0.0005"
- ◆ Butonlar: on/off, zero, mm/inç, ABS, değer setleme
- ◆ Veri çıkışı (Kablo kodu:100-15)
- ◆ Paslanmaz çelik