

Deđiřtirilebilir ubuksuz Derinlik Mikrometreleri

Seri 128

- 4 mm lm kolu.
- Cırcır durdurma sabit lm kuvveti sađlar.
- lm ubuđu kilitleme.
- Karbur model mevcuttur.



128-101



128-102



Metrik

No.	lm ara- lıđı [mm]	z- nrlk	İzin Verilen Maksimum Hata J MPE	lm yz- nn dzlem- selliđi (ta- ban)	lm yz- nn dzlem- selliđi (u- buk)	Referans yzeyi ve lm ubu- đu arasında pa- rallellik	Taban (WxT)	Ađırlık [g]
128-101	0 - 25	0,01 mm	± 3 m	1,3 m	0,3 m	5 m	63,5 x 16 mm	200
128-102	0 - 25	0,01 mm	± 3 m	2 m	0,3 m	5 m	101,6 x 16 mm	250

Metrik

Karbur ulu lm ubuđu

No.	lm ara- lıđı [mm]	z- nrlk	İzin Verilen Maksimum Hata J MPE	lm yz- nn dzlem- selliđi (ta- ban)	lm yz- nn dzlem- selliđi (u- buk)	Referans yzeyi ve lm ubu- đu arasında pa- rallellik	Taban (WxT)	Ađırlık [g]
128-103	0 - 25	0,01 mm	± 3 m	1,3 m	0,3 m	5 m	63,5 x 16 mm	200
128-104	0 - 25	0,01 mm	± 3 m	2 m	0,3 m	5 m	101,6 x 16 mm	250