Digimatic Screw Thread Micrometers with Interchangeable Tips

Functions	Series 326
Data output	●
ABS / INC (INC ZERO)	●
Auto Power OFF after 20 min. non use	●
Low voltage alarm	●
Function lock	●
HOLD	●
2 x PRESET	●

Series 326

This Digimatic Screw Thread Micrometer should be used with optional, interchangeable, anvils/spindle-tips that allow you to measure a wide range of metric/unified and Whitworth screw-thread pitch diameters.

A metric (unified) 60° setting standard is included with all models except those measuring range from 0-25 mm.

Dust- and Water-Protected

TÜVRheinland CERTIFIED

www.tuv.com ID 0000040191

IP65

Specifications

Display	LCD, character height 7,5 mm
Measuring face	Interchangeable anvil/ spindle inserts (optional)
Measuring spindle	With spindle lock, ø 6,35 mm, spindle pitch 0,5 mm
Scale	Thimble and sleeve satin chrome finish
Power supply	1 battery SR-44
Battery life	Approx. 2,4 years
Delivered	Including box, key, 1 battery, setting standard (from 25 mm upward) interchangeable tips are optional

Standard accessories

No.	Description
167-261	Setting Standard Screw Thread Micrometer, 60°, Length: 25mm
167-262	Setting Standard Screw Thread Micrometer, 60°, Length: 50mm
167-263	Setting Standard Screw Thread Micrometer, 60°, Length: 75mm



326-251-30 with optional accessories



Interchangeable anvils/spindle tips in matching pairs (optional accessories)

Metric

No.	Range [mm]	Digital step	Max. Permissible Error E MPE	Measuring force [N]	A [mm]	B [mm]	Mass [g]
326-251-30	0–25	0,001 mm	±4 µm	5-10	39,5	25	350
326-252-30	25–50	0,001 mm	±4 µm	5-10	64,5	32	380
326-253-30	50–75	0,001 mm	±4 µm	5-10	90	45	470
326-254-30	75–100	0,001 mm	±5 µm	5-10	115,6	65	510

All products to be sold to commercial customers.
Product illustrations are without obligation. Product descriptions, in particular any and all technical specifications, are only binding when explicitly agreed upon.

Mitutoyo