



$\lambda=25^\circ$
 $\gamma=12^\circ$

Type
N

DIN
327

ISO
1641

Z
2


İKİ AĞIZLI KISA DELİK FREZESİ DIN 327

C220

HSS

FİYAT USD

D	l	L	d h6	Z	
3	5	49	6	2	
4	7	51	6	2	
5	8	52	6	2	
6	8	52	6	2	
7	10	60	10	2	
8	11	61	10	2	
9	11	61	10	2	
10	13	63	10	2	
11	13	70	12	2	
12	16	73	12	2	
13	16	73	12	2	
14	16	73	12	2	
15	16	73	12	2	
16	19	79	16	2	
18	19	79	16	2	
20	22	88	20	2	
22	22	88	20	2	
24	26	102	25	2	
25	26	102	25	2	
26	26	102	25	2	
28	26	102	25	2	
30	26	102	25	2	

TEKNİK ÖZELLİKLERİ

HSS


Type
N

Genel kullanım içindir.
Çekme dayanımı 900 MPa'a
kadar olan malzemeler için.

HSS

Yüksek hız çeliği

KULLANIM ALANI

- Alaşımsız çelikler (180 HB)
- Yapı çelikleri (Sertlik:24 Hrc)
- Sementasyon nitrasyon çelikleri (Sertlik:27,1 Hrc)
- Dökme demir (Max.240 HB)
- Dökme demir (Min.240 HB)
- Alüminyum ve alaşımları (152 HB)
- Bakır ve alaşımları (Sertlik:22,2 Hrc)
- Alüminyum ve alaşımları (152 HB)