



$\lambda=25^\circ$
 $\gamma=12^\circ$
Type
NDIN
327ISO
1641Z
2

İKİ AĞIZLI UZUN FREZE DIN 327					C222
					HSS
D e8	l	L	d h6	Z	FİYAT USD
3	11	63	6	2	
4	11	63	6	2	
5	13	68	6	2	
6	13	68	6	2	
7	16	80	10	2	
8	19	88	10	2	
9	19	88	10	2	
10	22	95	10	2	
11	22	102	12	2	
12	26	110	12	2	
13	26	110	12	2	
14	26	110	12	2	
15	26	110	12	2	
16	32	123	16	2	
18	32	123	16	2	
20	38	141	20	2	
TEKNİK ÖZELLİKLERİ					 
Type N Genel kullanım içindir. Çekme dayanımı 900 MPa'a kadar olan malzemeler için.		KULLANIM ALANI		HSS Yüksek hız çeliği • Alaşımsız çelikler (180 HB) • Yapı çelikleri (Sertlik:24 Hrc) • Sementasyon nitrasyon çelikleri (Sertlik:27,1 Hrc) • Dökme demir (Max.240 HB) • Dökme demir (Min.240 HB) • Alüminyum ve alaşımları (152 HB) • Bakır ve alaşımları (Sertlik:22,2 Hrc) • Alüminyum ve alaşımları (152 HB)	