SERIES 218 WIRELESS HIGH PRECISION DIGITAL INDICATOR

Certificate Charge

- Built-in bluetooth
- Absolute encoder, the original data remains after power off
- Reading in digital and analog
- Supplied with cable for communication
- Button: data output, tolerance, data preset, data hold, measuring direction change, max./min./TIR, power off time, on/off, mm/inch, resolution adjustment
- Power: rechargeable battery, for 24 hours continuous working(full charge)



218-010-01W



218-025-01W

VIDEO

Lifting lever (Included)






display can be rotated by 320°



Cable (Included)



unit: mm



0-50.8mm


Contact points **(optional)**




Series **270**

Application





0-12.7mm



0-25.4mm

Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	Back
218-010-01W	12.7mm/0.5"	0.0001mm/0.00001" 0.001mm/0.00005" 0.01mm/0.0005"	1.5μm	1μm	Ruby	flat
218-025-01W	25.4mm/1"		1.8μm	1μm	Ruby	flat

Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	Back
218-010-11W	12.7mm/0.5"	0.0005mm/0.00002" 0.001mm/0.00005" 0.01mm/0.0005"	3μm	1.5μm	Carbide	flat
218-025-11W	25.4mm/1"		3μm	1.5μm	Carbide	flat
218-050-11W	50.8mm/2"		3μm	1.5μm	Carbide	flat

With manufacturer inspection certificate