
SERIES 575 CERAMIC SETTING RING

- For zero setting of inside micrometers, three points internal micrometers and bore gages
- Size difference (difference between the ordered size and the size marked on the setting ring when supplied):
  For example, the ordered size is Ø20.15mm, the size marked on the setting ring when supplied may be Ø20.155mm
- Made of ceramic, extremely wear resistance and corrosion resistance, dimensional stability



575-028-01



CUSTOM-MADE
Can supply custom setting rings from Ø3.00mm to Ø40.00mm, for example, Ø15.50mm

Roundess and taper (standard accuracy)

Diameter(mm)	Roundness	Taper
Ød≤30	0.5μm	1μm
30<Ød≤40	0.8μm	1.5μm

Reference size

Diameter(Ød)	Size difference
3<Ød≤5	±10μm
5<Ød≤10	±10μm
10<Ød≤15	±10μm
15<Ød≤20	±10μm
20<Ød≤25	±10μm
25<Ød≤32	±10μm
32<Ød≤40	±10μm

Code	Size(mm)
575-003-01	Ø3
575-004-01	Ø4
575-005-01	Ø5
575-006-01	Ø6
575-007-01	Ø7
575-008-01	Ø8
575-009-01	Ø9
575-010-01	Ø10

Code	Size(mm)
575-011-01	Ø11
575-012-01	Ø12
575-013-01	Ø13
575-014-01	Ø14
575-015-01	Ø15
575-016-01	Ø16
575-017-01	Ø17
575-018-01	Ø18

Code	Size(mm)
575-019-01	Ø19
575-020-01	Ø20
575-021-01	Ø21
575-022-01	Ø22
575-023-01	Ø23
575-024-01	Ø24
575-025-01	Ø25
575-026-01	Ø26

Code	Size(mm)
575-027-01	Ø27
575-028-01	Ø28
575-029-01	Ø29
575-030-01	Ø30
575-031-01	Ø31
575-032-01	Ø32
575-033-01	Ø33
575-034-01	Ø34

Code	Size(mm)
575-035-01	Ø35
575-036-01	Ø36
575-037-01	Ø37
575-038-01	Ø38
575-039-01	Ø39
575-040-01	Ø40