SERIES CFN COATING THICKNESS GAUGE

- Integrated F and N type probe
- F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel)
  N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
- Adjusting the display direction automatically
- With um/mil unit conversion
- Automatic power on/ off
- With back light
- With manufacturer inspection certificate



CFN3500B

SPECIFICATION

Code	CFN3500B	CFN5000B	CFN10000B
Range	0~3500μm	0~5000μm	0~10000μm
Accuracy	2μm(0~100μm)		
	2+3%(≥100μm)		
Resolution	0.1μm/1μm/10μm		
Min. measuring area	25×25mm		
Min. curvature	convexity: 5mm; concave: 25mm		
Min substrate thickness	magnetic material: 0.2mm; non magnetic material: 0.05mm		
Memory	100 sets		
Power supply	AA batteries		
Dimension(L×W×H)	112×63×29mm		
Weight	85g		

INCLUDED ACCESSORIES

Main unit	1pc
Calibration foil	1set
Calibration base	1set
AA battery	2pcs