
SERIES ESF MANUAL 360° SWIVEL ENDOSCOPE

Data output | Charge

- The cable can be seperated from the main unit
- The cable with lens can be rotated at 360°
- With abjustable LED light





ESF0615

FRONT VIEW ( )

Code	Probe diameter	Cable length
ESF0410	3.9mm	1m
ESF0415	3.9mm	1.5m
ESF0420	3.9mm	2m
ESF0430	3.9mm	3m
ESF0440	3.9mm	4m
ESF0450	3.9mm	5m
ESF0610	6mm	1m
ESF0615	6mm	1.5m
ESF0620	6mm	2m
ESF0630	6mm	3m
ESF0640	6mm	4m
ESF0650	6mm	5m
ESF0660	6mm	6m
ESF0670	6mm	7m

SIDE VIEW ( )

Code	Probe diameter	Cable length
ESF0410S	3.9mm	1m
ESF0415S	3.9mm	1.5m
ESF0420S	3.9mm	2m
ESF0430S	3.9mm	3m
ESF0610S	6mm	1m
ESF0615S	6mm	1.5m
ESF0620S	6mm	2m
ESF0630S	6mm	3m
ESF0640S	6mm	4m
ESF0650S	6mm	5m

SPECIFICATION

Cable type	steel wired weaved cable
Dust/waterproof probe	IP67
Camera pixel	1M pixel
Picture resolution	1280x720
Bend control	manual joystick
Frame rate	30fps
Illumination	adjustable LED
Display size	3.5inch LCD,Max.100,000Lux
Max.magnification	4X
Data output	HDMI/USB
Video format	JPEG/MOV
Memory	16G TF card
Power supply	rechargeable battery(for 8 hours working)
Weight	550g

INCLUDED ACCESSORIES

Main unit with cable	1pc
16G TF card	1pc
Card reader	1pc
AC/DC adapter	1pc
USB cable	1pc

OPTIONAL ACCESSORIES

Cable with probe	CABLE-xxxx (products code)
Magnet, Hook, Mirror (1 set, only for 6mm probe)*	ESS-MHM

* Should be bought with main unit