DATA OUTPUT

# DIGITAL INSIDE POINT CALIPERS

depth stop **6143** (optional)








**1121-150A**
**type A**



**1121-150B**
**type B**

- Non waterproof
- Measure groove diameter
- Resolution: 0.01mm/0.0005"
- Buttons type A: on/off, set, mm/inch, preset (+, -)
  type B: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code **6143**, for calipers with c=16mm)





**Preset (no need to add the width of the jaws on the reading), with data interface** (mm)

| Code | Range | Type | Accuracy | L | a | b | c | d | D | Wireless transmitter (optional) |
|---|---|---|---|---|---|---|---|---|---|---|
| **1121-150A** | 24-150mm/0.94-6" | A | ±0.04mm | 250 | 5 | 12 | 16 | 28 | Ø2 | **7315-25** (receiver is needed) |
| **1121-1501** | 35-150mm/1.38-6" | A | ±0.05mm | 250 | 6 | 17.5 | 16 | 60 | Ø2 | |
| **1121-200A** | 25-200mm/0.98-8" | A | ±0.04mm | 310 | 5 | 12.5 | 16 | 37 | Ø2 | |
| **1121-2001** | 40-200mm/1.57-8" | A | ±0.05mm | 310 | 7 | 20 | 16 | 70 | Ø3 | |
| **1121-300A** | 30-300mm/1.18-12" | A | ±0.07mm | 410 | 5 | 15 | 16 | 50 | Ø2 | |
| **1121-3001A** | 50-300mm/1.97-12" | A | ±0.07mm | 410 | 8 | 25 | 16 | 77 | Ø3 | |
| **1121-500A** | 40-500mm/1.57-20" | A | ±0.07mm | 680 | 5 | 20 | 24 | 90 | Ø3 | **7315-22** (receiver is needed) |
| **1121-5001** | 60-500mm/2.36-20" | A | ±0.08mm | 680 | 10 | 30 | 24 | 120 | Ø3 | |
| **1121-5002** | 80-500mm/3.15-20" | A | ±0.08mm | 680 | 16 | 40 | 24 | 150 | Ø3 | |

**Preset (no need to add the width of the jaws on the reading), built-in wireless (receiver code 7315-2/3/6/7/8/9 is needed)**

| Code | Range | Type | Accuracy | L | a | b | c | d | D |
|---|---|---|---|---|---|---|---|---|---|
| **1121-150AWL** | 24-150mm/0.94-6" | A | ±0.04mm | 250mm | 5mm | 12mm | 16mm | 28mm | Ø2mm |
| **1121-1501WL** | 35-150mm/1.38-6" | A | ±0.05mm | 250mm | 6mm | 17.5mm | 16mm | 60mm | Ø2mm |
| **1121-200AWL** | 25-200mm/0.98-8" | A | ±0.04mm | 310mm | 5mm | 12.5mm | 16mm | 37mm | Ø2mm |
| **1121-2001WL** | 40-200mm/1.57-8" | A | ±0.05mm | 310mm | 7mm | 20mm | 16mm | 70mm | Ø3mm |
| **1121-300AWL** | 30-300mm/1.18-12" | A | ±0.07mm | 410mm | 5mm | 15mm | 16mm | 50mm | Ø2mm |
| **1121-3001AWL** | 50-300mm/1.97-12" | A | ±0.07mm | 410mm | 8mm | 25mm | 16mm | 77mm | Ø3mm |
| **1121-500AWL** | 40-500mm/1.57-20" | A | ±0.07mm | 680mm | 5mm | 20mm | 24mm | 90mm | Ø3mm |
| **1121-5001WL** | 60-500mm/2.36-20" | A | ±0.08mm | 680mm | 10mm | 30mm | 24mm | 120mm | Ø3mm |
| **1121-5002WL** | 80-500mm/3.15-20" | A | ±0.08mm | 680mm | 16mm | 40mm | 24mm | 150mm | Ø3mm |

**No preset (need to add the width of the jaws on the reading)**

| Code | Range | Type | Accuracy | L | a | b | c | d | D |
|---|---|---|---|---|---|---|---|---|---|
| **1121-150B** | 50-150mm/1.97-6" | B | ±0.06mm | 270mm | 8mm | 25mm | 20mm | 90mm | Ø3mm |
| **1121-200B** | 60-200mm/2.36-8" | B | ±0.06mm | 320mm | 10mm | 30mm | 20mm | 100mm | Ø3mm |
| **1121-300B** | 60-300mm/2.36-12" | B | ±0.07mm | 420mm | 10mm | 30mm | 20mm | 110mm | Ø3mm |