ATTENTION: RECHARGEABLE BATTERY, FOR 12 HOURS CONTINUOUS WORKING

INDUCTIVE DIGITAL COMPARATOR (HIGH ACCURACY)

VIDEO | IP54 WATERPROOF | DATA OUTPUT






2149-2



- Built-in wireless transmission
- IP54 dust/waterproof
- Reading in digital and analog
- Display can be rotated by 320°
- Can store 10 set parameters, and the parameter can be searched and recalled
- 999 groups value can be stored
- Touch sensor: use the sensor to transmit data, avoiding press the button to cause deformation of the dial indicator stand and affect the zero position
- Button function: on/off, zero, data hold, measuring direction change, inch/metric conversion, data preset, absolute/incremental measurement, max./min./TIR measurement, tolerance Go and No-Go display, data output, analog pointer resolution and range change, print data
- Power: rechargeable battery, for 12 hours continuous working
- Ruby probe
- Data output
- Optional accessory:
  wireless receiver (code **2149-RE**, transmission distance is 2 meters),
  printer (code **ISF-DF-PRINTER**)

max./min./TIR



max./min./TIR measurement

printer (**optional**)



wireless receiver (**optional**)



Code	Range	Resolution	Accuracy	Hysteresis	Repeatability	Measuring force
2149-2	2mm/0.08"	0.1μm/0.000005"	0.5μm	0.2μm	0.3μm	0.8-1N

JEWELED BEARING | SHOCK PROOF | INSPECTION CERTIFICATE

DIAL COMPARATOR


INSIZE PLUS

10

- Meet DIN879-1
- Shockproof
- Jeweled bearing
- Overtravel: 3mm
- Shadow free dial face cover
- Supplied with limit pointers
- Initial measuring force 1.2N
- Optional accessory:
  lifting lever (code **6289-150**)



2881-01





lifting lever (**optional**)



Code	Range	Graduation	Accuracy	Hysteresis	Dial reading	Maximum measuring force	Cap	Remark
2881-01*	0.1mm	0.001mm	1.2μm	0.5μm	50-0-50	1.5N	cannot lift	flat back

*Supplied with manufacturer inspection certificate