300mm High Precision Profile Projector

Description

- High precision profile projector, classic design and high performance
- With a 300mm projector
- According to enterprise standard
- Applicable for workpiece direct and comparative measurement in a faster manner



Art.No.(erect image)		5292-3015N		5292-3020N	
Axis X travel		150 mm		200 mm	
Axis Y travel		100 mm		100 mm	
Axis Z travel		90 mm(Focusing)			
Glass worktable		148x206 mm		148x256 mm	
Metal worktable		258x308 mm		258x358 mm	
Resolution(X/Y axis)		0.5μm			
Indication error		E1XY≤(3+L/200)μm			
Projector screen		Dia.: 300 mm			
Rotary range		0°-360°			
Resolution		1′/ 0.01°			
Lens	Magnification	10X (Standard)	20X (Optional)	50X (Optional)	
	Objective view	30 mm	15 mm	6 mm	
	Working distance	80 mm	67.7 mm	51.4 mm	
Power supply		AC 100V/60Hz; 220V/50Hz			
Power		150W			
Weight		165 kg		168 kg	
Size		988x563x1157 mm		988x563x1157 mm	

400mm High Precision Profile Projector

Description

- High precision profile projector, classic design and high performance
- With a 400mm projector
- According to enterprise standard
- Applicable for workpiece direct and comparative measurement in a faster manner



Art.No.(erect image)		5292-4020N	5292-4025N	5292-4030N	
Axis X travel		200 mm	250 mm	300 mm	
Axis Y travel		100 mm	150 mm	200 mm	
Axis Z travel		100mm(Focusing)			
Glass worktable		198x306 mm	198x306 mm	356x248 mm	
Metal worktable		308x408 mm	308x408 mm	458x358 mm	
Resolution(X/Y axis)		0.5μm			
Indication error		E1XY≤(3+L/200)μm			
Projector screen		Dia.: 400 mm			
Rotary range		0°-360°			
Resolution		1′/ 0.01°			
Lens	Magnification	10X (Standard)	20X (Optional)	50X (Optional)	
	Objective view	40 mm	20 mm	8 mm	
	Working distance	80 mm	67.7 mm	51.4 mm	
Power supply		AC 110V/60Hz; 220V/50Hz			
Power		150W			
Weight		230 kg	230 kg	230 kg	
Size		1003x617x1309 mm	1003x617x1309 mm	1003x617x1309 mm	