# Magnetic Stand





## Description

- Super locking power
- For dial indicators shank φ6mm/8mm and with dovetail for dial test indicators
- With fine adjustment
- Prismatic magnetic base with ON/OFF switch(aluminium switch)
- Packed in cardbox

## Overall Dimension(mm)

| Range | a | b | c | d | e | L1 | L2 |
|---|---|---|---|---|---|---|---|
| 60x50x55mm | 50 | 60 | 55 | 10 | 12 | 227 | 175 |
| 73x50x55mm | 50 | 73 | 55 | 16 | 16 | 262 | 250 |

| Art No. | Magnetic Force | Base(Lxwxh) | Main Stem | Branch Stem | Barcode |
|---|---|---|---|---|---|
| 7131-80 | 80Kg | 60x50x55mm | 12x175mm | 10x165mm | 6972727951870 |
| 7131-100 | 100Kg | 73x50x55mm | 16x250mm | 16x200mm | 6972727951887 |

# Universal Magnetic Stand





## Description

- Super locking power
- For dial indicators shank φ6mm/8mm and with dovetail for dial test indicators
- With fine adjustment
- Prismatic magnetic base with ON/OFF switch (aluminium switch)
- Packed in cardbox

| Art No. | Magnetic Force | Base(Lxwxh) | Arm Length | Barcode |
|---|---|---|---|---|
| 7129-130 | 130Kg | 117x50x55mm | 635mm | 6972727951849 |

# Hydraulic Magnetic Stand





## Description

- Robust hydraulic locking mechanism and adjustable oil pressure
- Blackened shank and arm
- 8mm clamping hole and dovetail with fine adjustment for dial indicators
- Prismatic base with magnetic ON/OFF switch

## Overall Dimension(mm)

| Range | a | b | c | L1 | L2 |
|---|---|---|---|---|---|
| 60x50x55mm | 50 | 60 | 55 | 195 | 132 |
| 73x50x55mm | 50 | 73 | 55 | 195 | 132 |

| Art No. | Magnetic Force | Base Size | Arm Size | Barcode |
|---|---|---|---|---|
| 7137-80 | 80Kg | 60x50x55 mm | 350 mm | 6972727959111 |
| 7137-100 | 100Kg | 73x50x55 mm | 350 mm | 6972727959128 |