High Precision Digital Indicator With Bt



Description

- According to GB/T18761
- Large display,clear reading
- ABS encoding grating measuring sytem, up to micrometer
- Built-in bluetooth 5.0 module to make wireless data transmission available
- Built-in rechargeable battery
- With flat cover,stem ¢ 8h6
- Adapter
- Delivered with a manual
- Delivered with an inspection report
- Fancy plastic box
- ON/FF,Reset,Data transmission
- Data locking,Menu modes

Menus conversion

- F0=Normal measuring mode
- F1=Relative/Absolute measuring mode
- F2=mm/inch
- F3=Preset
- F4=Extreme value measuring mode
- F5=Tolerance setting - base value
- F6=Tolerence setting - lower limit
- F7=Tolerance setting - upper limit
- F8= Counting direction setting
- F9=Auto POWER OFF setting

Smart software and mobile phone APP

- Easy to install
- A couple of indicators can work at the same time
- To control and operate it via APP
- To collect and analyze data via PC software
- Suitable for more application scenarios

Bluetooth

- Bluetooth 5.0
- Lower power consumption, compatible with old versions
- Wider coverage,Accurate positioning
- Transmission speed 2-4 times faster

Art.No.	Range	Resolution	Accuracy	Hysteresis Error	Barcode
4208-512BT	0-12.7 mm	0.0005 mm	0.003 mm	0.0015 mm	6974804570509
4208-525BT	0-25.4 mm	0.0005 mm	0.003 mm	0.0015 mm	6974804570516
4208-550BT	0-50.8 mm	0.0005 mm	0.003 mm	0.0015 mm	6974804570523

