IP66 Water-Proof Workshop Digital Caliper





Description

- Attention: Be sure to keep the caliper away from heavy magnet or magnetic area
- With magnetic measuring system
- IP66 protection, water and dust resistant
- Stainless steel, hardened,With fine adjustment
- With REL , mm/inch and ABS three buttons
- Zero setting,mm/inch convenient at any position
- Low battery alarm
- Deliver in plastic box with 3V CR2032 battery and inspection report

Overall dimension(mm)

Range	a	c	d	h
0-300x0.01mm/100mm	100	10	18	24
0-500x0.01mm/150mm	150	10	18	24
0-1000x0.01mm/150mm	150	10	24	31
0-500x0.01mm/100mm	100	10	18	24
0-600x0.01mm/100mm	100	10	18	24
0-600x0.01mm/150mm	150	10	18	24
0-800x0.01mm/100mm	100	10	24	31
0-800x0.01mm/150mm	150	10	24	31
0-800x0.01mm/200mm	200	10	24	31
0-800x0.01mm/300mm	300	10	24	42

Art No.	Range	Reading	Length Of Jaw	Accuracy Error	Inside Measuring	Barcode
213-8487	300mm/12"	0.01mm/0.0005"	100mm	±0.05mm	20 mm	6971570718487
213-8494	500mm/20"	0.01mm/0.0005"	150mm	±0.06mm	20 mm	6971570718494
2210-501	500mm/20"	0.01mm/0.0005"	100 mm	±0.06 mm	20 mm	6972727951436
2210-601	600 mm/24"	0.01mm/0.0005"	100 mm	±0.06 mm	20 mm	6972727951443
2210-600	600 mm/24"	0.01mm/0.0005"	150 mm	±0.06 mm	20 mm	6972727951450
2210-801	800mm/32"	0.01mm/0.0005"	100 mm	±0.06 mm	20 mm	6972727951467
2210-800	800mm/32"	0.01mm/0.0005"	150 mm	±0.07 mm	20 mm	6972727951474
2210-802	800mm/32"	0.01mm/0.0005"	200 mm	±0.07 mm	20 mm	6972727951481
2210-803	800mm/32"	0.01mm/0.0005"	300 mm	±0.14 mm	20 mm	6972727951498
213-8500	1000mm/40"	0.01mm/0.0005"	150mm	±0.07mm	20 mm	6971570718500

Horizontal Digital Scale





Description

- Displacement measurement, worktable and lathe postioning etc
- Reset at any position,Made of stainless steel
- Both ends with fixed black holder
- LCD display,With Zero memory function
- 1.5V battery
- Delivered with holders installed on the back of the frame
- ON/OFF,Reset,mm/inch

Overall Dimension(mm)

Range	L	a	b	c	d	e
0-100mm	215	16	4	36	6	24
0-150mm	273	16	4	36	6	24
0-200mm	323	16	4	36	6	24
0-300mm	444	16	4	36	6	24
0-500mm	682	24	5.5	45	8	32
0-600mm	782	24	5.5	45	8	32
0-1000mm	1240	31	10.5	60	10	40

Art No.	Range	Reading	Indication Error	Barcode
4500-100B	100 mm	0.01mm	0.03 mm	6972727959067
4500-150B	150 mm	0.01mm	0.03 mm	6974804579519
4500-200B	200 mm	0.01mm	0.03 mm	6974804579526
4500-300B	300 mm	0.01mm	0.04 mm	6974804579533
4500-500B	500 mm	0.01mm	0.05 mm	6974804579540
4500-600B	600 mm	0.01mm	0.05 mm	6974804579557
4500-1000B	1000 mm	0.01mm	0.07 mm	6974804579564