

Bore Gauge With Carbide Tip









Description

- Made in and originated from europe
- Used for measurements bore diameter
- Interchangeable fixed tips
- Handle with insulation chamber
- ø8mm clamping shank for indicators
- Packed in wooden box


Overall dimension(mm)

Range	A	B	Remark
5-10 mm	145	4.8	
10-20 mm	160	9.5	
15-35 mm	200	8	
30-100 mm	275	13	
50-160 mm	280	13	
50-210 mm	397	13	
100-300 mm	375	15	
15-35 mm	94	8	Short rod

Art.No.	Range	Reading	Indication Error	Repeatability	Net weight	Barcode	
4115-010A-01	5-10 mm	0.01mm	±0.005 mm	0.003 mm	60 g	6976367672683	
4115-020A-01	10-20 mm	0.01mm	±0.005 mm	0.003 mm	100 g	6976367672690	
4115-035A-01	15-35 mm	0.01mm	±0.003 mm	0.001 mm	80 g	6976367672706	
4115-100A-01	30-100 mm	0.01mm	±0.003 mm	0.001 mm	190 g	6976367672713	
4115-160A-01	50-160 mm	0.01mm	±0.003 mm	0.001 mm	220 g	6976367672720	
4115-210A-01	50-210 mm	0.01mm	±0.003 mm	0.001 mm	270 g	6976367672737	
4115-300A-01	100-300 mm	0.01mm	±0.003 mm	0.001 mm	460 g	6976367672744	
4115-035A-AC-01	15-35 mm	0.01mm	±0.003 mm	0.001 mm	50 g	6976367672751	Short rod

Bore Gauge For Blind Holes









Description

- Made in and originated from europe
- Used for measurements at a minimum distance from the bottom
- Handle with insulation chamber
- ø8mm clamping shank for indicators
- Packed in wooden box

Overall dimension(mm)

Range	A	B
16-35 mm	94	8
25-60 mm	155	8
50-150 mm	162	13
100-300 mm	250	15

Art.No.	Range	Reading	Measuring Depth	Indication Error	Repeatability	Net weight	Barcode
4116-035-01	16-35 mm	0.01mm	35mm	±0.005 mm	0.001 mm	50 g	6976367672768
4116-060-01	25-60 mm	0.01mm	130 mm	±0.005 mm	0.001 mm	100 g	6976367672775
4116-150-01	50-150 mm	0.01mm	150 mm	±0.005 mm	0.001 mm	190 g	6976367672782
4116-300-01	100-300 mm	0.01mm	230 mm	±0.005 mm	0.001 mm	400 g	6976367672799