Small Bore Gauge





Description

- Made in and originated from europe
- Manual recall of the mechanism, to facilitate entry into the holes
- Handle with insulation chamber
- ø8mm clamping shank for indicators
- Packed in wooden box

Overall dimension(mm)

Range	A	B	C
5-10 mm	145	4.8	70
10-20 mm	160	9.5	70

Art.No.	Range	Reading	Measuring Depth	Indication Error	Repeatability	Net weight	Barcode
4115-010-SD01	5-10 mm	0.01mm	70 mm	±0.003 mm	0.002 mm	60 g	6976367672805
4115-020-SD01	10-20 mm	0.01mm	70 mm	±0.003 mm	0.002 mm	100 g	6976367672812

Bore Gauge With Ceramic Tips

Description

- With ceramic tips, wear-resistant
- Deliver with inspection report
- Prime plastic box



WITH DIAL INDICATORS

Art No.	Range		Reading	Meauring depth	Accuracy error	Repeatability	Barcode
4106-C18	10-18 mm	Dial indicator 0-5mm	0.01 mm	100 mm	±0.012 mm	0.003 mm	6976367672355
4106-C35	18-35 mm	Dial indicator 0-10mm	0.01 mm	150 mm	±0.015 mm	0.003 mm	6976367672362
4106-C50	35-50 mm		0.01 mm	150 mm	±0.018 mm	0.003 mm	6976367672379
4106-C160	50-160 mm		0.01 mm	150 mm	±0.018 mm	0.003 mm	6976367672348
4106-C250	160-250 mm		0.01 mm	250 mm	±0.018 mm	0.003 mm	6976367672386
4106-C450	250-450 mm		0.01 mm	250 mm	±0.018 mm	0.003 mm	6976367672393

WITH DIGITAL INDICATORS

Art No.	Range		Reading	Meauring depth	Accuracy error	Repeatability	Barcode
4206-C18	10-18 mm	Digital indicator 0-12.7mm	0.002 mm	100 mm	±0.012 mm	0.003 mm	6976367674939
4206-C35	18-35 mm		0.002 mm	150 mm	±0.015 mm	0.003 mm	6976367674946
4206-C50	35-50 mm		0.002 mm	150 mm	±0.018 mm	0.003 mm	6976367674953
4206-C160	50-160 mm		0.002 mm	150 mm	±0.018 mm	0.003 mm	6976367674960
4206-C250	160-250 mm		0.002 mm	250 mm	±0.018 mm	0.003 mm	6976367674977
4206-C450	250-450 mm		0.002 mm	250 mm	±0.018 mm	0.003 mm	6976367674984

WITH DIGITAL INDICATORS

Art No.	Range		Reading	Meauring depth	Accuracy error	Repeatability	Barcode
4206-C181	10-18 mm	Digital indicator 0-12.7mm	0.001 mm	100 mm	±0.005 mm	0.002 mm	6976367674991
4206-C351	18-35 mm		0.001 mm	150 mm	±0.006 mm	0.002 mm	6976367675004
4206-C501	35-50 mm		0.001 mm	150 mm	±0.007 mm	0.002 mm	6976367675011
4206-C1601	50-160 mm		0.001 mm	150 mm	±0.007 mm	0.002 mm	6976367675028
4206-C2501	160-250 mm		0.001 mm	250 mm	±0.007 mm	0.002 mm	6976367675035
4206-C4501	250-450 mm		0.001 mm	250 mm	±0.007 mm	0.002 mm	6976367675042